

IN THE CLAIMS:



RECEIVED  
MAR 27 2003  
Technology Center 2600

1. (Currently Amended) A system for connecting peripheral devices to a computer, comprising:

- a host computer system, wherein said host computer system includes a CPU and memory;
- a first parallel bus coupled to the host computer system;
- a primary bridge coupled to the first parallel bus, wherein said primary bridge includes parallel interface circuitry for interfacing to the first parallel bus;
- a second parallel bus located remotely from said host computer system;
- one or more peripheral devices coupled to the second parallel bus; and
- a secondary bridge coupled to said second parallel bus, wherein said secondary bridge is located remotely from said host computer system, wherein said secondary bridge includes parallel interface circuitry for interfacing to said second parallel bus; and

a serial bus coupled between said primary bridge and said secondary bridge, wherein the serial bus includes a first end and a second end, wherein said first end of said serial bus is coupled to said primary bridge and said second end of said serial bus is coupled to said secondary bridge;

wherein said primary bridge and said secondary bridge are configured to transmit a parallel bus cycle over said serial bus, wherein said parallel bus cycle includes an address phase and a data phase, wherein said address phase includes a command value and an address value, and wherein said data phase includes a first set of byte enable values and a data value;

wherein said primary bridge is configured to receive said parallel bus cycle, wherein said primary bridge is configured to generate a first command packet that corresponds to said address phase, wherein said primary bridge is configured to generate a plurality of data packets that each correspond to said parallel bus cycle, wherein said first command packet includes a second set of byte enable values, and wherein said primary bridge is configured to set said second set of byte enable values to a set of

predetermined values prior to generating said plurality of data packets, wherein said predetermined values comprise predicted values of the first set of byte enable values.

2. (Original) The system of claim 1, wherein said primary bridge is configured to compare said first set of byte enable values to said set of predetermined values, and wherein said primary bridge is configured to generate a second command packet if said first set of byte enable values differs from said set of predetermined values.

3. (Original) The system of claim 2, wherein said primary bridge is configured to store said first set of byte enable values in said second command packet if said first set of byte enable values differs from said set of predetermined values.

a' 4. (Original) The system of claim 2, wherein said primary bridge is configured to discard said first command packet if said first set of byte enable values differs from said set of predetermined values.

5. (Original) The system of claim 1, wherein said primary bridge is configured to set said second set of byte enable values irrespective of said first set of byte enable values.

6. (Original) The system of claim 1, wherein said primary bridge further includes a FIFO queue, wherein said FIFO queue includes a head and a tail, wherein said primary bridge is configured to store said command value and said address value in said FIFO queue upon receipt of said address phase, and wherein said primary bridge is configured to generate said first command packet when said command value reaches said head of said FIFO queue.

7. (Original) The system of claim 6, wherein said primary bridge is configured to store said first set of byte enable values and said data value in said FIFO queue upon receipt of said data phase, wherein said primary bridge is configured to compare said first set of byte enable values to said set of predetermined values when said first set of byte

enable values reaches said head of said FIFO queue, and wherein said primary bridge is configured to generate a second command packet if said first set of byte enable values differs from said set of predetermined values.

8. (Original) The system of claim 7, wherein said second command packet includes a third set of byte enable values, and wherein said primary bridge is configured to set said third set of byte enable values equal to said first set of byte enable values if said first set of byte enable values differs from said set of predetermined values.

9. (Original) The system of claim 1, wherein a first of said plurality of data packets corresponds to said address value, wherein a second of said plurality of data packets corresponds to said data value, and wherein said primary bridge is configured to transmit said first command packet and said plurality of data packets to said secondary bridge over said serial bus.

10. (Original) The system of claim 1, wherein said first parallel bus comprises a Peripheral Component Interconnect (PCI) bus, and wherein said second parallel bus comprises a Peripheral Component Interconnect (PCI) bus.

11. (Currently Amended) A method for ~~for~~ transmitting a parallel bus cycle over a serial bus in a computer system, the method comprising:

generating said parallel bus cycle in a host computer, wherein said parallel bus cycle includes an address phase and a data phase, wherein said address phase includes a command value and an address value, and wherein said data phase includes a first set of byte enable values and a data value;

transmitting said parallel bus cycle from said host computer to a primary bridge over a first parallel bus;

generating a first command packet in said primary bridge, wherein said first command packet includes a ~~second~~ predicted set of byte enable values, and wherein said first command packet corresponds to said address phase of said parallel bus cycle; and

generating a plurality of data packets in said primary bridge, wherein each of said plurality of data packets corresponds to said parallel bus cycle;

~~wherein said generating said first command packet includes setting said second set of byte enable values to a set of predetermined values prior to generating said plurality of data packets.~~

12. (Currently Amended) The method of claim 11, further comprising:

comparing said first set of byte enable values to said set of ~~predetermined~~ predicted values in said primary bridge; and

generating a second command packet in said primary bridge if said first set of byte enable values differs from said set of ~~predetermined~~ predicted values, wherein said second command packet includes said first set of byte enable values.

Q! 13. (Currently Amended) The method of claim 12, further comprising:

discarding said first command packet in said primary bridge if said first set of byte enable values differs from said set of ~~predetermined~~ predicted values.

14. (Currently Amended) The method of claim 11, further comprising:

transmitting information from said primary bridge to a secondary bridge over a serial bus;

recreating said parallel bus cycle in said secondary bridge in response to receiving said information from said primary bridge;

transmitting said parallel bus cycle from said secondary bridge to a peripheral device over a second parallel bus;

comparing said first set of byte enable values to said set of ~~predetermined~~ predicted values in said primary bridge; and

generating a second command packet in said primary bridge if said first set of byte enable values differs from said set of ~~predetermined~~ predicted values.

15. (Currently Amended) The method of claim 14, wherein said second command packet includes a third set of byte enable values, wherein said generating said

a' second command packet includes setting said third set of byte enable values equal to said first set of byte enable values if said first set of byte enable values differs from said set of ~~predetermined~~ predicted values, and wherein said transmitting said information includes transmitting said second command packet and said plurality of data packets if said first set of byte enable values differs from said set of ~~predetermined~~ predicted values.

Please cancel claim 16.

~~16~~ 17. (Original) The method of claim 11, further comprising:  
storing said command value and said address value in a FIFO queue in said primary bridge upon receipt of said address phase; and  
performing said generating said first command packet when said address phase reaches a head of said FIFO queue.

a<sup>2</sup> ~~17~~ 18. (Original) The method of claim ~~17~~ <sup>16</sup>, further comprising:  
storing said first set of byte enable values and said data value in said FIFO queue in said primary bridge upon receipt of said data phase;  
comparing said first set of byte enable values to said set of predetermined values when said first set of byte enable values reaches said head of said FIFO queue; and  
generating a second command packet in said primary bridge if said first set of byte enable values differs from said set of predetermined values.

~~18~~ 19. (Currently Amended) The method of claim ~~18~~ <sup>17</sup>, wherein said second command packet includes a third set of byte enable values, wherein said generating said second command packet includes setting said third set of byte enable values equal to said first set of byte enable values if said first set of byte enable values differs from said set of predetermined values, and wherein said transmitting said information includes transmitting said second command packet and said plurality of data packets if said first set of byte enable values differs from said ~~set of predetermined values~~ predicted set of byte enable values.

19  
20. (Original) The method of claim 11, wherein a first of said plurality of data packets corresponds to said address value, wherein a second of said plurality of data packets corresponds to said data value, and wherein said transmitting said information includes transmitting said first command packet and said plurality of data packets.

20  
21. (Currently Amended) The method of claim 11, wherein said ~~first~~ parallel bus cycle comprises a Peripheral Component Interconnect (PCI) bus cycle, ~~and wherein said second parallel bus comprises a Peripheral Component Interconnect (PCI) bus.~~

21  
22. (Original) A bus bridge configured to transmit a parallel bus cycle over a serial bus in a computer system, wherein said bus bridge is configured to receive said parallel bus cycle, wherein said parallel bus cycle includes an address phase and a data phase, wherein said address phase includes a command value and an address value, and wherein said data phase includes a first set of byte enable values and a data value, comprising:

Q<sup>2</sup>  
a queue configured to store said address phase and said data phase;

a transmitter pipeline coupled to said queue, wherein said transmitter pipeline is configured to generate a first command packet in response to an address phase reaching a head of said queue, wherein said first command packet includes a second set of byte enable values, and wherein said transmitter pipeline is configured to set said second set of byte enable values to a set of predetermined values prior to said data phase reaching said head of said queue; and

a transmitter coupled to said transmitter pipeline, wherein said transmitter is configured to transmit a plurality of packets over said serial bus in a serial format.

22  
23. (Original) The bus bridge of claim <sup>21</sup>~~22~~, wherein said transmitter pipeline is configured to compare said first set of byte enable values to said set of predetermined values when said data phase reaches said head of said queue, and wherein said transmitter pipeline is configured to generate a second command packet if said first set of byte enable values differs from said set of predetermined values.

<sup>23</sup>  
~~24~~ (Original) The bus bridge of claim <sup>22</sup>~~23~~, wherein said transmitter pipeline is configured to store said first set of byte enable values in said second command packet if said first set of byte enable values differs from said set of predetermined values.

<sup>24</sup>  
~~25~~ (Original) The bus bridge of claim <sup>23</sup>~~24~~, wherein said transmitter pipeline is configured to generate a first data packet corresponding to said address value stored in said queue, wherein said transmitter pipeline is configured to generate a second data packet corresponding to said data value stored in said queue, and wherein said transmitter is configured to transmit said second command packet, said first data packet, and said second data packet if said first set of byte enable values differs from said set of predetermined values.

<sup>25</sup>  
~~26~~ (Original) The bus bridge of claim <sup>24</sup>~~25~~, wherein said transmitter is configured to transmit said first command packet, said first data packet, and said second data packet if said first set of byte enable values does not differ from said set of predetermined values.

<sup>26</sup>  
~~27~~ (Original) The bus bridge of claim <sup>22</sup>~~23~~, wherein said transmitter pipeline is configured to discard said first command packet if said first set of byte enable values differs from said set of predetermined values.

<sup>27</sup>  
~~28~~ (Original) The bus bridge of claim <sup>21</sup>~~22~~, wherein said transmitter pipeline is configured to set said second set of byte enable values irrespective of said first set of byte enable values.

<sup>28</sup>  
~~29~~ (Original) The bus bridge of claim <sup>21</sup>~~22~~, wherein said queue includes a FIFO queue.

<sup>29</sup>  
~~30~~ (Original) The bus bridge of claim <sup>21</sup>~~22~~, wherein said transmitter pipeline is configured to generate a first data packet corresponding to said address value stored in said queue, wherein said transmitter pipeline is configured to generate a second data

packet corresponding to said data value stored in said queue, and wherein said transmitter is configured to transmit said first command packet, said first data packet, and said second data packet.

Q2  
~~30~~  
~~31~~. (Original) The bus bridge of claim ~~22~~, wherein said bus bridge comprises a PCI bus bridge.

Please cancel claims 32 and 33.

Please add the following new claims:

~~34~~  
34. (New) A method for transmitting a parallel bus cycle over a serial bus in a system, the method comprising:

generating said parallel bus cycle in a host computer, wherein said parallel bus cycle includes an address phase and a data phase, wherein said address phase includes a command value and an address value, and wherein said data phase includes a first set of byte enable values and a data value;

Q3  
transmitting said parallel bus cycle from said host computer to a first interface over a first parallel bus;

generating a first packet in said first interface, wherein said first packet includes a predicted set of byte enable values, wherein the first packet is generated prior to availability of the first set of byte enable values;

receiving the first set of byte enable values after said generating the first packet;

comparing the first set of byte enable values to the set of predicted values; and

generating a second packet in the first interface if the first set of byte enable values differs from the set of values, wherein said second packet includes said first set of byte enable values.

~~32~~  
~~35~~. (New) The method of claim ~~34~~,  
~~31~~

23  
wherein the first packet is discarded if said first set of byte enable values differs  
from said set of predicted values.

---